


**Fusion Factory**  
COMPACT





## Fusion Factory COMPACT

### for BASF Ultrafuse 316L

Ultrafuse® 316L is an innovative filament to produce 316L grade stainless steel parts. It is designed for ultimate ease of handling on conventional Fused Filament Fabrication 3D printers. BASF Ultrafuse® 316L combines greater freedom of design with a lower total cost of ownership – printing metal parts easier, faster and affordable.



#### GENERAL

##### Dimension (WxDxH)

1.200mm x 1.200mm x 2.000mm

##### Connection

400 V / 32 A

##### Complete time for debinding & sintering

< 24h

#### CATALYTIC DEBINDING UNIT

##### Max. temperature

1.550 °C

##### Working volume

150mm x 150mm x 150mm

##### Gas flow

Nitrogen, 0 ... 10l/min

#### Acid flow

0 ... 3 ml/min

The system is also available as Single Debinding System with extended working space 250mm x 250mm x 250mm

#### SINTER FURNACE

##### Max. temperature

1.550 °C

##### Working volume

150mm x 150mm x 150mm

##### Atmospheres

Nitrogen, Hydrogen, Vacuum, Air

The system is also available as Single Furnace System with extended working space 250mm x 250mm x 250mm

## Contact Us

### XERION BERLIN LABORATORIES® GmbH

Gross-Berliner Damm 84 A, D-12487 Berlin | Germany

Tel. +49 (0) 30 - 20 09 70 20

E-Mail [fusionfactory@xerion.de](mailto:fusionfactory@xerion.de)

Web [www.xerion.de](http://www.xerion.de)

